

Nexus 810 Low VOC Vinyl Adhesive

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 810 Low VOC Vinyl Adhesive is a high performance low VOC acrylic based adhesive designed for the installation of commercial and domestic sheet vinyl. It has excellent plasticiser resistance and is formulated to provide quick initial grab and exhibit excellent 're-bond' characteristics.

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect final bond. All surfaces must be prepared in accordance with current Australian Standards 1884-2012 Floor Coverings Resilient Sheet including moisture testing. **Nexus 810** can be applied to concrete substrates with moisture content up to 85% RH (relative humidity) and falling. This RH should be measured by deploying the in-situ probe method (in accordance with ASTM F2170). **Nexus 810** can be applied to concrete substrate with pH readings up to 10.0. It is recommended that all highly absorbent sub floors be primed with **Nexus 510 Acrylic Floor & Wall Primer** prior to the application of adhesive. The minimum sub floor temperature prior to commencing preparation or adhesive application is 10°C.

DIRECTION FOR USE

Apply adhesive using a 1.6mm x 1.6mm x 1.6mm "V" notched spreader. Coverage should be in the vicinity of 5m² per litre. Some domestic sheet vinyl may require a fine 1.6mm x 0.8mm x 0.8mm "U" notched trowel to prevent adhesive 'show through'.

Adhesive can be allowed to tack-up prior to placing the floor covering into the wet film of adhesive. Tack-up time will depend on atmospheric conditions. Always ensure complete transfer of adhesive to the floorcovering has occurred. Complete installation according to manufacturer's instructions. Roll installation on completion with the recommended weight roller.

Do not allow heavy traffic for 24 hours.

Seams of domestic vinyl should be sealed using **Nexus 460 Vinyl Seam Sealer**.

CLEAN UP

Clean tools immediately after use with warm soapy water.

Dried adhesive may be softened using a suitable solvent like **Nexus 490**.

Typical properties

Base:	Acrylic
Solids:	Approx 70%
Shelf Life:	12 months in sealed container at 20°C
Packaging:	15 Litre pails

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

March 2019

Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road

Dandenong South VIC 3175 Australia

Tel +61 3 9706 4022

Fax +61 3 9706 4122

info@nexusadhesives.com.au

www.nexusadhesives.com.au