

580 Timber Underlay Adhesive

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 580 is high solids timber underlay Adhesive with Low VOC. It is a high bond strength water based adhesive designed for the installation of Hardboard/Timber underlays to timber substrates.

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect the final bond.

All surfaces must be prepared in accordance with current Australian Standards 1884-2012 Floor Coverings Resilient Sheet including moisture testing.

Ensure timber subfloor is absorbent to allow adhesive to dry.

The minimum sub floor temperature prior to commencing preparation or adhesive application is 10°C.

DIRECTION FOR USE

Spread adhesive with a 2.4mm x 2.4mm x 2.4mm 'V' Notched trowel.

Only spread about 2 square meters at time and then install underlay in to the wet adhesive film.

Always ensure a 100% adhesive transfer to the back of underlay.

Roll underlay with correct roller weight. 40kg roller is suitable.

Staple or nail underlay as required prior to adhesive setting.

Complete installation according to underlay manufacturer's instructions.

CLEAN UP

Clean tools immediately after use with warm soapy water.

Dried adhesive may be softened from tools using a suitable solvent such as Nexus 490.

Typical Properties.

Base	EVA Polymer
Solids	Approx 80%
Shelf Life	12 months in sealed container at 20°C
Packaging	15 Litre pails
Coverage	Approx 2 – 2.5m ² per Lt

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

November 2012

Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
info@nexusadhesives.com.au
www.nexusadhesives.com.au