

Nexus 180 Skirting Contact

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 180 is a water-based contact adhesive with excellent plasticiser migration resistance. It is suitable for fixing vinyl skirting and other common flooring materials where a quick contact bond is required to plaster, timber and metal substrates.

METHOD OF APPLICATION

To obtain the best results, the materials to be bonded should be dry, clean and free from dust, grit, oil, grease and other contaminants that may affect final bond. On shiny/glossy products, it is recommended to give the bonding surface a light sanding and cleaning prior to applying adhesive.

Apply a **thin** even coat of adhesive to both surfaces by brush or roller. Always coat the least absorbent surface first. On highly porous surfaces a second application may be required.

Allow the adhesive coating to dry and become tacky. (Drying times may vary from 20 minutes to 1 hour, depending on the application method used, the adsorption into the substrate, the temperature and relative humidity of the environment).

Place the surfaces together making sure that they are correctly positioned beforehand as no adjustment is possible after the surface has met.

Press both surfaces together, making sure sufficient pressure is applied to bring both surfaces into close contact. Use a hand roller or stair tool to complete installation. Slight warming of PVC product (up to 50 °C) will increase adhesion to substrates.

CLEAN UP

Clean tools immediately after use with warm soapy water.

Dried adhesive may be softened using a **Nexus Adhesive Remover** or **Nexus 490 Solvent Cleaner**.

IMPORTANT: Do not use Nexus 490 Solvent Cleaner directly on finish floorcovering, as the solvent cleaner can potentially cause damage to the surface.

Typical Properties

Appearance	White brush-able liquid
Coverage	8 – 10 m ² per litre
Open Time	20 – 30 minutes at 50% Relative Humidity and 21 °C
Curing time	24 hours.
Packaging	4 Litres
Shelf Life	12 months in sealed container at 20 °C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

November 2021

Nexus Adhesives Pty Ltd
ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au