

Nexus 430 Construction Adhesive

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 430 Construction adhesive is specifically developed for bonding most common materials used in the construction industry.

Nexus 430 is a high solids product that forms a very strong bond to most common building products including timber, plasterboard, MDF, particleboard, timber sheet flooring, concrete and metals.

METHOD OF APPLICATION

All surfaces must be clean & sound, free of dust and any other contaminants that may affect bond.

Cut cartridge tip, fit nozzle and cut end to desired opening. (Approx. 4-5mm) Apply beads of adhesive to one surface of product to be bonded. Press the two surfaces to be bonded firmly together. Apply pressure to keep the two surfaces in contact while adhesive cures. Fix with sufficient nails, screws or clamping to maintain contact.

CLEAN UP

Remove any wet adhesive with suitable solvent cleaner like **Nexus 490** and **Nexus Adhesive Remover**. When cured remove by mechanical means.

Dried adhesive may be softened using a **Nexus Adhesive Remover** or **Nexus 490 Solvent Cleaner**.

IMPORTANT: Do not use Nexus 490 Solvent Cleaner directly on finish floorcovering, as the solvent cleaner can potentially cause damage to the surface.

TYPICAL PROPERTIES

Appearance	Thick brown liquid in cartridge
Coverage	10 - 20m ² per litre
Open Time	0 – 10 minutes
Curing Time	24 hours
Packaging	320g cartridge
Shelf Life	12 months in sealed container at 20 °C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.

November 2021

Nexus Adhesives Pty Ltd
ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au