

Nexus 460 Vinyl Seam Sealer

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 460 Vinyl Seam Sealer is a solvent based adhesive designed for the chemically welding of domestic vinyl sheet flooring seams.

METHOD OF APPLICATION

All seams must be clean and dry prior to seam sealing.

Transfer **460 Vinyl Seam Sealer** to applicator bottle.

Place masking tape over centre of seam, cut tape at seam in floor.

Starting at one end of seam insert applicator tip into seam and apply a continuous bead along the entire length of the seam.

Allow approx. 10 minutes and remove tape.

Avoid excess seam sealer on surface of floor covering.

CLEAN UP

Clean tools immediately after use with **Nexus 490** solvent cleaner.

Nexus 490 is not suitable for use on Vinyl, Carpets or any finished surface.

TYPICAL PROPERTIES

Appearance	Light yellow thin liquid
Coverage	Up to 250 linear meters per 500 mL bottle
Drying Time	Approx. 10 minutes at 50% Relative Humidity and 21 °C
Curing Time	24 Hours
Packaging	500 mL
Shelf Life	12 months in sealed container at 20 °C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

November 2021

Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au