

Nexus 990 Carpet Latex

TECHNICAL DATA SHEET

DESCRIPTION & USES

Nexus 990 Carpet Latex is a natural latex compound for sealing raw edges of carpet and installing felt underlay to substrates. The latex helps prevent with loss of tufts and unraveling after seams have been trimmed.

METHOD OF APPLICATION

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect the final bond. All surfaces must be prepared in accordance with the current Australian Standards 1884 - Floor coverings resilient sheet and 2455.1 & 2455.2 - Textile floor coverings installation practice including moisture testing. The minimum sub floor temperature prior to commencing preparation or the application of **Nexus 990** is 10°C.

DIRECTION OF USE

Prior to joining carpet seams with heat bond tape or seam sealer, apply **Nexus 990** to edge of carpet and allow drying. When used to install felt underlay to subfloors apply a liberal amount to the subfloor and install underlay into wet latex.

CLEAN UP

Clean excess adhesive immediately using a lightly damp cloth.

Clean tools immediately after use with warm soapy water.

Dried adhesive may be softened using a **Nexus Adhesive Remover** or **Nexus 490 Solvent Cleaner**.

IMPORTANT: Do not use **Nexus 490** Solvent Cleaner directly on finish floorcovering, as the solvent cleaner can potentially cause damage to the surface.

TYPICAL PROPERTIES

Appearance	Thin white liquid with ammonia odour
Coverage	Up to 70 linear metres per litre
Curing Time	24 Hours
Packaging	1, 4 and 15 Litre
Shelf Life	12 months in sealed container at 20 °C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

November 2021

Nexus Adhesives Pty Ltd
ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au