

Nexus 510 Acrylic Floor & Wall Primer

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 510 Primer is a water based acrylic primer designed to prime absorbent substrates prior to the application of water-based adhesives.

METHOD OF APPLICATION

Nexus 510 Primer is designed for priming most highly absorbent substrates such as concrete, timber, solid plaster, plasterboard, cement sheet and cementitious screeds.

SURFACE PREPARATION

All surfaces to be primed should be dry, smooth, and free of any contaminants in accordance with current AS 1884. It is highly recommended that all absorbent sub floors be primed with **Nexus 510 Primer** prior to the application of adhesive.

The minimum sub floor temperature prior to commencing preparation or primer application is 10°C.

APPLICATION

Nexus 510 Primer should be applied evenly over the entire sub floor by soft broom or brush.

Highly absorbent sub floors may require a second coat of **Nexus 510 Primer**. Allow first coat to dry prior to applying further coats.

CLEAN UP

Clean tools immediately after use with warm soapy water.

TYPICAL PROPERTIES

| | |
|--------------------|---|
| Appearance | Thin white liquid |
| Coverage | up to 8 – 10 m ² /L, depending on absorbance of substrate. |
| Drying time | Approx. 30 minutes at 50% Relative Humidity and 21 °C. |
| Packaging | 15 Litre |
| Shelf Life | 12 months in sealed container at 20 °C |

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

November 2021

Nexus Adhesives Pty Ltd

ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au