

Nexus 470 Carpet Seam Sealer

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 470 Carpet Seam Sealer is a solvent based adhesive designed for the bonding of seams in direct stick carpet installation.

METHOD OF APPLICATION

IMPORTANT: Ensure the ambient temperature is between 10°C and 30°C with low to moderate humidity, conditions outside this range may lead to failures caused by humidity blushing.

All seams must be clean and dry prior to seam sealing. Apply a 2 – 3 mm bead of adhesive along the bottom edge of the carpet seam and join carpet.

Ensure seam sealer does not get on pile of carpet.

CLEAN UP

Clean tools immediately after use with **Nexus 490** solvent cleaner.

Nexus 490 is not suitable for use on Vinyl, Carpets or any finished surface.

TYPICAL PROPERTIES

Appearance	Light yellow liquid
Coverage	Up to 70 linear meters per 1L bottle
Drying Time	Approx. 10 minutes at 50% Relative Humidity and 21 °C
Curing Time	24 Hours
Packaging	1 Litre
Shelf Life	12 months in sealed container at 20 °C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

June 2024

Nexus Adhesives Pty Ltd
ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au