

Nexus Grippa-Fast 200 Adhesive

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 200 is ideal for bonding carpet gripper, woods, metal trims, metal nosing, aluminium & many other types of products where a quick bond is required to concrete, timber and most other common building substrates. **Nexus 200** has excellent resistance to high temperatures and water.

METHOD OF APPLICATION

SURFACE PREPARATION

To obtain the best results, all surfaces should be clean & sound, free of dust and any other contaminants that may affect bond.

DIRECTION OF USE

Apply thin bead of adhesive to one surface. Press the two surfaces to be bonded firmly together. Pressure may need to be applied to keep the two surfaces in contact while adhesive cures. Large extrusions should also be secured with appropriate fixing screws.

Nexus 200 has a moisture-cure system, allow approx. 1 hour curing time. This process may be accelerated by spraying a light mist of water to one of the surfaces. Thick beads will take longer to cure and will have a weaker bond than a thinner bead. The thicker the bead of **Nexus 200** the more the product will tend to foam.

CLEAN UP

Remove any wet adhesive with suitable solvent cleaner solvent like **Nexus 490** and **Nexus Adhesive Remover** before it cures. When cured remove by mechanical means.

Dried adhesive may be softened using a **Nexus Adhesive Remover** or **Nexus 490 Solvent Cleaner**.

IMPORTANT: Do not use Nexus 490 Solvent Cleaner directly on finish floorcovering, as the solvent cleaner can potentially cause damage to the surface.

TYPICAL PROPERTIES

Appearance	Brown thin liquid
Coverage	Up to 250 linear metres per bottle
Open Time	0 - 10 minutes at 50% Relative Humidity and 21 °C
Curing time	1 hour at 50% Relative Humidity and 21 °C
Packaging	500 mL bottle
Shelf Life	6 months in sealed container at 20 °C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

August 2024

Nexus Adhesives Pty Ltd
ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au