

Nexus 810 Low VOC Vinyl Adhesive

TECHNICAL DATA SHEET

DESCRIPTION & USES

Nexus 810 Low VOC Vinyl Adhesive is a high-performance adhesive designed for the installation of commercial and domestic sheet vinyl. It has excellent plasticiser resistance and is formulated to provide quick initial grab and exhibit excellent 're-bond' characteristics. This product can also be used for wall sheet vinyl. Internal use only.

METHOD OF APPLICATION

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, absorbent, and free of any contaminants that may affect final bond. All surfaces must be prepared in accordance with current Australian Standards 1884 Floor Coverings Resilient Sheet including moisture testing. It is recommended that all highly absorbent substrates be primed with **Nexus 510 Acrylic Floor & Wall Primer** prior to the application of adhesive. The minimum sub floor temperature prior to commencing preparation or adhesive application is 10°C.

DIRECTION OF USE

Apply adhesive using a 1.6mm x 1.6mm x 1.6mm "V1" notched spreader. Coverage should be in the vicinity of 5m² per litre. Some domestic sheet vinyl and wall vinyl may require a fine 1.6mm x 0.8mm x 0.8mm "U" notched trowel to prevent adhesive 'show through'.

Adhesive can be allowed to tack-up prior to placing the floor covering into the wet film of adhesive. Tack-up time will depend on atmospheric conditions. Always ensure complete transfer of adhesive to the floorcovering has occurred. Complete installation according to manufacturer's instructions. Roll installation on completion with the recommended weight roller.

Do not allow heavy traffic for 24 hours.

Seams of domestic vinyl should be sealed using **Nexus 460 Vinyl Seam Sealer**.

CLEAN UP

Clean excess adhesive immediately using a lightly damp cloth.

Clean tools immediately after use with warm soapy water.

Dried adhesive may be softened using a **Nexus Adhesive Remover** or **Nexus 490 Solvent Cleaner**.

IMPORTANT: Do not use Nexus 490 Solvent Cleaner directly on finish floorcovering, as the solvent cleaner can potentially cause damage to the surface.

TYPICAL PROPERTIES

Appearance	Thick cream coloured paste
Coverage	Up to 5 m ² per Litre using "V1" notched spreader.
Open Time	Approx. 30 minutes at 50% Relative Humidity and 21 °C
Curing Time	72 Hours
Packaging	15 Litre pails
Shelf Life	12 months in sealed container at 20 °C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

August 2024

Nexus Adhesives Pty Ltd
ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au